

Kalibrierstifte werden zum Ausmessen von Ziehsteinen oder zum Abkalibrieren von Messwerkzeugen benötigt. EUROMICRON fertigt Kalibrierdrähtchen mit zwei ballistischen Spitzen aus Federstahldraht nach DIN 17223 Bl.1 / DIN 2076. Sie werden auf das jeweilige Maß gezogen und nach Vorgabe abgelängt.

Merkmale

- Kalibrierdrähtchen mit 2 ballistischen Spitzen
- Hohe Präzision

Die Kalibrierdrähte von EUROMICRON sind in folgenden Durchmessern lieferbar:

- 0,100 - 1,000 mm Abstufungen in 2 µm, 35 mm lang.
- 1,005 - 1,600 mm Abstufungen in 5 µm, 40 mm lang.
- Zwischenabmessungen auf Anfrage erhältlich

Kalibriestifte

- 0,500 - 6,600 mm Abstufungen in 10 µm, 80 mm lang.
- Zwischenabmessungen auf Anfrage erhältlich



Sizing wire

Sizing wire is used for die measuring or tool calibrating purposes. EUROMICRON is producing sizing wires with two ballistic tips made of spring steel wire acc. to DIN 17223, sheet 1 / DIN 2076. The wire is drawn to the desired size and cut off to obtain the required length.

Features

- Sizing wires with 2 ballistic tips
- High precision

EUROMICRON sizing wire may be supplied with the following diameters:

- 0.100 - 1.000 mm in graduations of 2 µm, length 35 mm.
- 1.005 - 1.600 mm in graduations of 5 µm, length 40 mm.
- Intermediate dimensions available on request.

Sizing pens

- 0.500 - 6.600 mm in graduations of 10 µm, length 80 mm.
- Intermediate dimensions available on request.

* Abmessung / Size

Verpackungseinheiten
Packing unit

50, 100, 250, 500, 1.000
Stück / pcs.

Anmerkung:
Andere Größen auf Anfrage

Note: Other sizes upon request

Artikelnummer Part number	Messbereich measurement range	Abstufungen measure steps	Längen length
KBDR-xxxx*-0035	0,100 - 1,000 mm	2 µm	35 mm
KBDR-xxxx*-0040	1,005 - 1,600 mm	5 µm	40 mm
KBST-xx00-xxx0-0080	0,500 - 6,600 mm	10 µm	80 mm